

ProLink LoRaWAN EndNode Modem HCI Specification (AS923)

Specification Version 2.0

Document ID: 4000/40140/0131

IMST GmbH
Carl-Friedrich-Gauß-Str. 2-4
47475 KAMP-LINTFORT
GERMANY



Document Information

File name	ProLink_LoRaWAN_EndNode_Modem_Region_AS923_HCI_Spec.docx
Created	2018-02-01
Total pages	12

Revision History

Version	Note
0.1	Created, Initial Version Reference: WiMOD LoRaWAN EndNode Modem HCI Spec V1.22
0.2	Reference: WiMOD LoRaWAN EndNode Modem HCI Spec V1.26 Chapter 2.1.2.1 updated
0.3	Update for RP002-1.0.1
1.0	Document renamed Reference: WiMOD LoRaWAN EndNode Modem HCI Spec V2.2 Reference: RP002-1.0.1 LoRaWAN® Regional Parameters document (LoRa Alliance).
2.0	Valid from firmware V3.0, Build Count 196 Document renamed to support the ProLink LoRaWAN FW Reference: ProLink LoRaWAN EndNode Modem HCI Spec Reference: RP002-1.0.1 LoRaWAN® Regional Parameters document (LoRa Alliance).

Aim of this Document

This document describes the ProLink LoRaWAN^{®1} EndNode Modem Host Controller Interface (HCI) protocol which is part of the ProLink LoRaWAN[®] EndNode Modem firmware. This firmware can be used in combination with the WiMOD LoRa radio module family.

¹ LoRa[®] is a registered trademark of Semtech Corporation. LoRaWAN[®] is a registered trademark of the LoRa Alliance[®].



Table of Contents

1. INTRODUCTION	4
1.1 Overview	4
2. APPENDIX	5
2.1 LoRaWAN® Multi Band Support	5
2.1.1 Radio Band Indices	5
2.1.2 Asia 923 – 1 Band	6
2.1.3 Asia 923 – 2 Band	7
2.1.4 Asia 923 – 3 Band	8
2.2 Proprietary LoRa® Communication Support	9
2.3 List of Abbreviations	10
2.4 List of References	10
3. REGULATORY COMPLIANCE INFORMATION	11
4. IMPORTANT NOTICE	12
4.1 Disclaimer	12
4.2 Contact Information	12



1. Introduction

1.1 Overview

This document is an extension to the ProLink LoRaWAN EndNode Modem HCI document [1], covering the changes included in the ProLink LoRaWAN EndNode Modem firmware for AS 923 MHz ISM Band.



2. Appendix

2.1 LoRaWAN® Multi Band Support

2.1.1 Radio Band Indices

Index	Band Description	Comments
10	AS923 – 1 (915 - 928 MHz) - Asia	Default setting
11	AS923 – 2 (920 - 923 MHz) - Asia	
12	AS923 – 3 (915 - 921 MHz) - Asia	



2.1.2 Asia 923 – 1 Band

2.1.2.1 Data Rate Indices

Index	Data Rate / Spreading Factor	Bandwidth	Indicative physical bit rate [bit/s]	Comments
0	LoRa / SF12	125 kHz	250	Only available if DwellTime set to 0 by the LoRaWAN server
1	LoRa / SF11	125 kHz	440	
2	LoRa / SF10	125 kHz	980	Default setting
3	LoRa / SF9	125 kHz	1760	
4	LoRa / SF8	125 kHz	3125	
5	LoRa / SF7	125 kHz	5470	
6	LoRa / SF7	250 kHz	11000	
7	FSK / 50kbps		50000	

2.1.2.2 Channel Indices

Index	Frequency Channel	Comments
0	923 200 000 Hz	Data Rates 0 - 5
1	923 400 000 Hz	Data Rates 0 - 5
128	923 200 000 Hz	Default Frequency for Rx2 Default Data Rate: 2



2.1.3 Asia 923 – 2 Band

2.1.3.1 Data Rate Indices

Index	Data Rate / Spreading Factor	Bandwidth	Indicative physical bit rate [bit/s]	Comments
0	LoRa / SF12	125 kHz	250	Only available if DwellTime set to 0 by the LoRaWAN server
1	LoRa / SF11	125 kHz	440	
2	LoRa / SF10	125 kHz	980	Default setting
3	LoRa / SF9	125 kHz	1760	
4	LoRa / SF8	125 kHz	3125	
5	LoRa / SF7	125 kHz	5470	
6	LoRa / SF7	250 kHz	11000	
7	FSK / 50kbps		50000	

2.1.3.2 Channel Indices

Index	Frequency Channel	Comments
0	921 400 000 Hz	Data Rates 0 - 5
1	921 600 000 Hz	Data Rates 0 - 5
128	921 400 000 Hz	Default Frequency for Rx2 Default Data Rate: 2



2.1.4 Asia 923 – 3 Band

2.1.4.1 Data Rate Indices

Index	Data Rate / Spreading Factor	Bandwidth	Indicative physical bit rate [bit/s]	Comments
0	LoRa / SF12	125 kHz	250	Only available if DwellTime set to 0 by the LoRaWAN server
1	LoRa / SF11	125 kHz	440	
2	LoRa / SF10	125 kHz	980	Default setting
3	LoRa / SF9	125 kHz	1760	
4	LoRa / SF8	125 kHz	3125	
5	LoRa / SF7	125 kHz	5470	
6	LoRa / SF7	250 kHz	11000	
7	FSK / 50kbps		50000	

2.1.4.2 Channel Indices

Index	Frequency Channel	Comments
0	916 600 000 Hz	Data Rates 0 - 5
1	916 800 000 Hz	Data Rates 0 - 5
128	916 600 000 Hz	Default Frequency for Rx2 Default Data Rate: 2

2.2 Proprietary LoRa® Communication Support

The ProLink LoRaWAN® EndNode Modem firmware for AS 923 MHz ISM Band does not support the proprietary LoRa® communication and therefore those services are not available.



2.3 List of Abbreviations

FW	Firmware
HCI	Host Controller Interface
LR	Long Range
LoRa	Long Range
RAM	Random Access Memory
RF	Radio Frequency
RSSI	Received Signal Strength Indicator
RTC	Real Time Clock
SLIP	Serial Line Internet Protocol
SNR	Signal to Noise Ratio
UART	Universal Asynchronous Receiver/Transmitter
WiMOD	Wireless Module by IMST

2.4 List of References

[1] ProLink_LoRaWAN_EndNode_Modem_HCI_Spec.pdf.

3. Regulatory Compliance Information

The use of radio frequencies is limited by national regulations. The radio module has been designed to comply with the European Union's R&TTE (Radio & Telecommunications Terminal Equipment) directive 1999/5/EC and can be used free of charge within the European Union. Nevertheless, restrictions in terms of maximum allowed RF power or duty cycle may apply.

The radio module has been designed to be embedded into other products (referred as "final products"). According to the R&TTE directive, the declaration of compliance with essential requirements of the R&TTE directive is within the responsibility of the manufacturer of the final product. A declaration of conformity for the radio module is available from IMST GmbH on request.

The applicable regulation requirements are subject to change. IMST GmbH does not take any responsibility for the correctness and accuracy of the aforementioned information. National laws and regulations, as well as their interpretation can vary with the country. In case of uncertainty, it is recommended to contact either IMST's accredited Test Center or to consult the local authorities of the relevant countries.

4. Important Notice

4.1 Disclaimer

IMST GmbH points out that all information in this document is given on an “as is” basis. No guarantee, neither explicit nor implicit is given for the correctness at the time of publication. IMST GmbH reserves all rights to make corrections, modifications, enhancements, and other changes to its products and services at any time and to discontinue any product or service without prior notice. It is recommended for customers to refer to the latest relevant information before placing orders and to verify that such information is current and complete. All products are sold and delivered subject to “General Terms and Conditions” of IMST GmbH, supplied at the time of order acknowledgment.

IMST GmbH assumes no liability for the use of its products and does not grant any licenses for its patent rights or for any other of its intellectual property rights or third-party rights. It is the customer’s duty to bear responsibility for compliance of systems or units in which products from IMST GmbH are integrated with applicable legal regulations. Customers should provide adequate design and operating safeguards to minimize the risks associated with customer products and applications. The products are not approved for use in life supporting systems or other systems whose malfunction could result in personal injury to the user. Customers using the products within such applications do so at their own risk.

Any reproduction of information in datasheets of IMST GmbH is permissible only if reproduction is without alteration and is accompanied by all given associated warranties, conditions, limitations, and notices. Any resale of IMST GmbH products or services with statements different from or beyond the parameters stated by IMST GmbH for that product/solution or service is not allowed and voids all express and any implied warranties. The limitations on liability in favor of IMST GmbH shall also affect its employees, executive personnel and bodies in the same way. IMST GmbH is not responsible or liable for any such wrong statements.

Copyright © 2022, IMST GmbH

4.2 Contact Information

IMST GmbH

Carl-Friedrich-Gauss-Str. 2-4
47475 Kamp-Lintfort
Germany

T +49 2842 981 0

F +49 2842 981 299

E wimod@imst.de

I www.wireless-solutions.de