

WiMOD LoRaWAN EndNode Modem HCI Specification (IL915)

Specification Version 0.2

Document ID: 4000/40140/0132

IMST GmbH

Carl-Friedrich-Gauß-Str. 2-4
47475 KAMP-LINTFORT
GERMANY



Document Information

File name	WiMOD_LoRaWAN_EndNode_Modem_IL915_HCI.docx
Created	2017-12-06
Total pages	9

Revision History

Version	Note
0.1	Created, Initial Version Reference: WiMOD LoRaWAN EndNode Modem HCI Spec V1.21
0.2	Chapter 2.1 updated

Aim of this Document

This document describes the changes of the Host Controller Interface (HCI) protocol which is part of the WiMOD LoRaWAN EndNode Modem firmware which supports the Israel band configuration. This firmware can be used in combination with the WiMOD LoRa radio module family.

Table of Contents

1. INTRODUCTION	4
1.1 Overview	4
2. APPENDIX	5
2.1 Multi Band Support	5
2.1.1 Radio Band Indices	5
2.1.2 Israel 915 MHz Band	6
2.2 List of Abbreviations	7
2.3 List of References	7
3. REGULATORY COMPLIANCE INFORMATION	8
4. IMPORTANT NOTICE	9
4.1 Disclaimer	9
4.2 Contact Information	9

1. Introduction

1.1 Overview

This document is an extension to the WiMOD LoRaWAN EndNode Modem HCI document [1], covering the changes included in the WiMOD LoRaWAN EndNode Modem firmware supporting the Israel band configuration.

IMST GmbH

2. Appendix

2.1 Multi Band Support

2.1.1 Radio Band Indices

Index	Band Description
40	IL 915 MHz - Israel

2.1.2 Israel 915 MHz Band

2.1.2.1 Data Rate Indices

Index	Data Rate / Spreading Factor	Bandwidth	Indicative physical bit rate [bit/s]
0	LoRa / SF12	125 kHz	250
1	LoRa / SF11	125 kHz	440
2	LoRa / SF10	125 kHz	980
3	LoRa / SF9	125 kHz	1760
4	LoRa / SF8	125 kHz	3125
5	LoRa / SF7	125 kHz	5470
6	LoRa / SF7	250 kHz	11000
7	FSK / 50kbps		50000

2.1.2.2 Channel Indices

Index	Frequency Channel	Comments
0	915 700 000 Hz	Data Rates 0 - 5
1	915 900 000 Hz	Data Rates 0 - 5
2	916 100 000 Hz	Data Rates 0 - 5
128	916 300 000 Hz	Default Frequency for Rx2 Default Data Rate: 0

2.2 List of Abbreviations

FW	Firmware
HCI	Host Controller Interface
LR	Long Range
LoRa	Long Range
RAM	Random Access Memory
RF	Radio Frequency
RSSI	Received Signal Strength Indicator
RTC	Real Time Clock
SLIP	Serial Line Internet Protocol
SNR	Signal to Noise Ratio
UART	Universal Asynchronous Receiver/Transmitter
WiMOD	Wireless Module by IMST

2.3 List of References

[1] WiMOD_LoRaWAN_EndNode_Modem_HCI_Spec.pdf.

3. Regulatory Compliance Information

The use of radio frequencies is limited by national regulations. The radio module has been designed to comply with the European Union's R&TTE (Radio & Telecommunications Terminal Equipment) directive 1999/5/EC and can be used free of charge within the European Union. Nevertheless, restrictions in terms of maximum allowed RF power or duty cycle may apply.

The radio module has been designed to be embedded into other products (referred as "final products"). According to the R&TTE directive, the declaration of compliance with essential requirements of the R&TTE directive is within the responsibility of the manufacturer of the final product. A declaration of conformity for the radio module is available from IMST GmbH on request.

The applicable regulation requirements are subject to change. IMST GmbH does not take any responsibility for the correctness and accuracy of the aforementioned information. National laws and regulations, as well as their interpretation can vary with the country. In case of uncertainty, it is recommended to contact either IMST's accredited Test Center or to consult the local authorities of the relevant countries.

4. Important Notice

4.1 Disclaimer

IMST GmbH points out that all information in this document is given on an “as is” basis. No guarantee, neither explicit nor implicit is given for the correctness at the time of publication. IMST GmbH reserves all rights to make corrections, modifications, enhancements, and other changes to its products and services at any time and to discontinue any product or service without prior notice. It is recommended for customers to refer to the latest relevant information before placing orders and to verify that such information is current and complete. All products are sold and delivered subject to “General Terms and Conditions” of IMST GmbH, supplied at the time of order acknowledgment.

IMST GmbH assumes no liability for the use of its products and does not grant any licenses for its patent rights or for any other of its intellectual property rights or third-party rights. It is the customer’s duty to bear responsibility for compliance of systems or units in which products from IMST GmbH are integrated with applicable legal regulations. Customers should provide adequate design and operating safeguards to minimize the risks associated with customer products and applications. The products are not approved for use in life supporting systems or other systems whose malfunction could result in personal injury to the user. Customers using the products within such applications do so at their own risk.

Any reproduction of information in datasheets of IMST GmbH is permissible only if reproduction is without alteration and is accompanied by all given associated warranties, conditions, limitations, and notices. Any resale of IMST GmbH products or services with statements different from or beyond the parameters stated by IMST GmbH for that product/solution or service is not allowed and voids all express and any implied warranties. The limitations on liability in favor of IMST GmbH shall also affect its employees, executive personnel and bodies in the same way. IMST GmbH is not responsible or liable for any such wrong statements.

Copyright © 2018, IMST GmbH

4.2 Contact Information

IMST GmbH

Carl-Friedrich-Gauss-Str. 2-4
47475 Kamp-Lintfort
Germany

T +49 2842 981 0

F +49 2842 981 299

E wimod@imst.de

I www.wireless-solutions.de